

BALING WIRE



Rewounds

black annealed/oiled
galvanized/unoiled



Everything about wires



Rewounds black annealed/oiled | galvanized/unoiled

Black annealed, oiled or galvanized, unoiled baling wire for automatic balers in spooled coils.



Rewounds - black annealed



Rewounds - soft galvanized

Quality

DIN EN ISO 16120-2, as per DIN EN 10218-2

Technical data

Size range: 2.00 mm – 4.00 mm

| | | | |
|---------------------------|-------------|----------|----------|
| Dimensions: | 20 kg | 40 kg | 46 kg |
| Inner diameter (conical): | 90 / 100 mm | 206 mm | 210 mm |
| Outer diameter: | 250 mm | 336 mm | 350 mm |
| Coil width: | 95 mm | 152 mm | 152 mm |
| Tolerance: | +/- 5 mm | +/- 6 mm | +/- 6 mm |

Packaging:

20 kg



50 rewounds packed on a EUR pallet, or per customer requirements

40 kg



27 rewounds packed on a EUR pallet, or per customer requirements



CONTACT US



Bracksieker Draht GmbH
Lammersbrink 24/25 | 49328 Melle
Telephone: +49 5427 9434-0
Telefax: +49 5427 9434-14
www.bracksieker.de | info@bracksieker.de