

BALING WIRE



# Quicklinks

galvanized | bright drawn/phosphated |  
coppered



Everything about wires



# Quicklinks

galvanized | bright drawn/phosphated | coppered  
(long and rolled version)

**Long version:** Quicklink wires made from high-tensile steel (1,600–1,800 N/mm<sup>2</sup>), with elongation < 5.0%, available in small bundles (125–150 pieces) stacked to large bundles, securely strapped with steel straps.

**Rolled version:** Small bundles (25–36 pieces), packed in large cartons on EUR pallets.



Quicklinks, rolled



Quicklinks long

## Quality

DIN EN ISO 16120-2, as per DIN EN 10218-2 / SAE1070 – SAE1085

## Technical data

Tensile strength:	1,600 – 1,800 N/mm <sup>2</sup>
Elongation:	< 5.00 %
Tolerance diameter:	-0.05 / + 0.03 mm
Size range:	2.45 – 3.80 mm
Length tolerance:	- 0 / + 2 mm or per customer requirement
Galvanized coating:	min. 40 g/m <sup>2</sup> (only applies to galvanized)

## Dimensions

Length:	2,200 – 4,700 mm
Total length of the quicklinks:	50 mm (+/- 1 mm)
Inner diameter quicklink head:	10 mm
Height quicklink head:	10-15 mm
Bundle outer diameter:	max. 780 mm

## Packaging

Small bundles tied with masking tape or cable ties, the ends of the small bundles are protected with PVC bags, packed in a large box on a EUR pallet and secured with steel straps or large bundles pressed with steel straps.




Small bundle with PVC bags



Rolled on EUR pallet



Small bundle to a large bundle on Euro pallet



## CONTACT US

 **Bracksieker**

Bracksieker Draht GmbH  
Lammersbrink 24/25 | 49328 Melle  
Telephone: +49 5427 9434-0  
Telefax: +49 5427 9434-14  
[www.bracksieker.de](http://www.bracksieker.de) | [info@bracksieker.de](mailto:info@bracksieker.de)