



Traverse wound coils

bright drawn | black annealed

stainless steel | high tensile wire



Everything about wires



Traverse wound coils

bright drawn | black annealed
stainless steel | high tensile wire

Bright drawn or galvanised wire, black annealed wire, bright drawn or galvanised high tensile wire and stainless steel wire in spooled traverse wound coils with lifting loops, secured with steel straps in four places, supplied in an uncoiled version.



Traverse wound coils - bright drawn



Traverse wound coils - black annealed

Quality bright drawn steel wires:	DIN EN ISO 16120-2, as per DIN EN 10218-2 / SAE1004 – SAE 1072
Quality stainless steel:	11.4301, 1.4404, 1.4541, 1.4571
Quality high-carbon:	DIN EN ISO 16120-2, as per DIN EN 10218-2, SL, SM, SH

Technical data	
Tensile strength:	Per your requirements
Elongation:	Per your requirements
Tolerance:	- 0.00 mm / + 0.08 mm or per your requirements
Surface blank variants:	Bright drawn, wet drawn, lubricated/waxed drawn
Size range bright drawn:	1.00 mm – 13.00 mm
Size range black annealed:	2.00 mm – 6.00 mm
Galvanized coating:	min. 25 – 375 g/m ² (class A-D) variable according to diameter

Dimensions		
Inner diameter:	Outer diameter:	Coil width:
40 – 47 cm	78 – 87 cm	approx. 50 cm

Weight:	250 kg, 500 kg, 1,000 kg coils or per requirements
---------	--

Packaging	
Coils of 1,000 kg, 4 x pressed with steel strips	
Loading lying on side with lifting rings upwards (“eye to the sky”), or loading sideways (“eye to the side”)	
	Eye to the sky (on pallet)
	Eye to the side (without pallet)



CONTACT US

 **Bracksieker**

Bracksieker Draht GmbH
Lammersbrink 24/25 | 49328 Melle
Telephone: +49 5427 9434-0
Telefax: +49 5427 9434-14
www.bracksieker.de | info@bracksieker.de

